

ARENA

AXIAL DECORATIVE FANS

Features



- o Wall and ceiling mounting.
- o UV resistant ABS plastic.
- o Easy maintenance.
- o Continuous operation.
- o Backdraft damper.
- o Ball bearing motor.
- o 5 year warranty.
- o Compatible with **Blauberg Design Konzept** decorative panels.



Air flow:
up to 174 m³/h
48 l/s



Power:
from 14 W
SFP:
from 0.33 W/l/s



Noise level:
from 33 dBA




Options



| Model | Arena 100 / Arena 125 | | | | |
|------------------|-----------------------|---|----|---|----|
| | S | T | ST | H | SH |
| Pull cord switch | • | | • | | • |
| Timer | | • | • | • | • |
| Humidity sensor | | | | • | • |

- o **Turn-off delay timer**
 - Adjustable delay time from 2 to 30 minutes.
- o **Humidity sensor**
 - Humidity sensor activation threshold is adjustable from 60 % to 90 %.

Overall dimensions and mounting




| Dimensions [mm] | Ø D | Ø D1 | L | L1 |
|-----------------|-----|------|-----|----|
| Arena 100 | 100 | 172 | 121 | 88 |
| Arena 125 | 125 | 172 | 122 | 88 |

Technical data

| Model | Arena 100 | Arena 125 |
|------------------------------------|-----------|-----------|
| Voltage [V] | 220-240 | 220-240 |
| Frequency [Hz] | 50 | 50 |
| Power [W] | 14 | 16 |
| Current [A] | 0.09 | 0.117 |
| RPM [min ⁻¹] | 2300 | 2400 |
| Air flow [m ³ /h (l/s)] | 92 (26) | 174 (48) |
| SFP [W/l/s] | 0.55 | 0.33 |
| Sound pressure level [dBA]* | 33 | 35 |
| Weight [kg] | 0.52 | 0.78 |

* Sound pressure level measured in free space at a distance of 3 meters from the fan.



Designation key

| | | |
|-------|-----------------|--------|
| Arena | 100 | H |
| Model | Spigot diameter | Option |

Accessories

| Duct system | Flexible air ducts | Grilles and hoods | Speed controllers | Clamps |
|-------------|--------------------|-------------------|------------------------|--------|
| | | | | |
| BlauPlast | BlauFlex | Decor, GM | CDT E0.5 MCD 60/0.3 | K, KZ |