

# Axis-F

## Axial inline fans

### Use

- Supply and extract ventilation systems installed in various premises.
- Ideal solution for boosting large air volumes at low aerodynamic resistance in the ventilation system.



**Air flow:**  
up to 15550 m<sup>3</sup>/h  
4320 l/s



**Power:**  
from 50 W



### Design

- Compact steel casing and impeller with a special polymer coating.
- Casing is equipped with connecting flanges for easy mounting into air duct.
- The fan is equipped with a terminal block for connection to power mains.

### Motor

- Two-, four-, six- or eight-pole asynchronous motor with external rotor and axial impeller.
- Single-phase (**E**) or three-phase (**D**) motor modifications.
- Equipped with ball bearings for longer service life.
- Integrated thermal protection with automatic restart.

### Speed control

- Step speed control with an external auto transformer (available upon separate order).

### Mounting

- The fan is installed in air ducts by connecting flanges on the fan casing.
- Power is supplied through an external terminal box.

AXIAL FANS

#### Designation key

Series	Dimension type	Motor Number of poles	Phase
Axis-F	200; 250; 300; 350; 400; 450; 500; 550; 630; 710; 800	2; 4; 6; 8	E: single-phase D: three-phase

#### Accessories

##### Speed controllers




CDR5E E... TP



CDR5E D... M

**Dimensions [mm]**

Type	∅ D	∅ D1	∅ D2	∅ d	B	L	Weight [kg]
Axis-F 200 2E	205	235	255	7.0	290	120	3.0
Axis-F 250 2E	260	286	306	7.0	340	150	3.9
Axis-F 250 4E	260	286	306	7.0	340	150	4.0
Axis-F 300 2E	310	356	382	7.0	410	160	6.2
Axis-F 300 4E	310	356	382	7.0	410	160	6.2
Axis-F 350 4E	362	395	421	9.5	450	160	7.7
Axis-F 400 4E	412	438	465	9.5	500	170	8.1
Axis-F 450 4E	462	487	515	9.5	550	200	9.1
Axis-F 450 6E	462	487	515	9.5	550	200	9.1
Axis-F 500 4E	515	541	570	9.5	600	220	11.0
Axis-F 500 6E	515	541	570	9.5	600	220	11.0
Axis-F 550 4E	565	605	636	11.5	660	230	13.9
Axis-F 550 6E	565	605	636	11.5	660	230	13.9
Axis-F 630 4E	645	674	715	11.5	740	250	16.4
Axis-F 630 6E	645	674	715	11.5	740	250	16.4
Axis-F 250 2D	260	286	306	7.0	340	150	3.9
Axis-F 250 4D	260	286	306	7.0	340	150	4.0
Axis-F 300 2D	310	356	382	7.0	410	160	5.7
Axis-F 300 4D	310	356	382	7.0	410	160	6.2
Axis-F 350 4D	362	395	421	9.5	450	160	7.7
Axis-F 400 4D	412	438	465	9.5	500	170	8.1
Axis-F 450 4D	462	487	515	9.5	550	200	9.1
Axis-F 450 6D	462	487	515	9.5	550	200	9.1
Axis-F 500 4D	515	541	570	9.5	600	220	11.0
Axis-F 500 6D	515	541	570	9.5	600	220	11.0
Axis-F 550 4D	565	605	636	11.5	660	230	13.9
Axis-F 550 6D	565	605	636	11.5	660	230	13.9
Axis-F 630 4D	645	674	715	11.5	740	250	16.4
Axis-F 630 6D	645	674	715	11.5	740	250	16.4
Axis-F 710 6D	725	767	805	11.5	835	250	30.0
Axis-F 710 8D	725	767	805	11.5	835	250	30.0
Axis-F 800 8D	800	845	880	11.5	910	280	40.0




**Technical data**

Parameters	Axis-F 200 2E		Axis-F 250 2E		Axis-F 250 4E		Axis-F 300 2E		Axis-F 300 4E		Axis-F 350 4E		Axis-F 400 4E	
Voltage [V]	1 ~ 230		1 ~ 230		1 ~ 230		1 ~ 230		1 ~ 230		1 ~ 230		1 ~ 230	
Frequency [Hz]	50	60	50	60	50	60	50	60	50	60	50	60	50	60
Power [W]	55	61	80	91	50	56	145	178	75	92	140	147	180	240
Current [A]	0.26	0.28	0.4	0.42	0.22	0.24	0.66	0.79	0.35	0.4	0.65	0.66	0.82	1.08
Maximum air flow [m³/h (l/s)]	860 (239)	875 (243)	1050 (292)	1150 (319)	800 (222)	865 (240)	2230 (619)	2280 (633)	1340 (372)	1475 (410)	2500 (695)	2650 (736)	3580 (995)	3890 (1081)
RPM [min⁻¹]	2300	2550	2400	2990	1380	1730	2300	2410	1350	1405	1380	1700	1380	1655
Sound pressure at 3 m [dBA]	48	49	50	51	38	39	53	54	44	45	46	47	53	54
Transported air temperature [°C]	-30...+60		-30...+50		-30...+60		-30...+50		-30...+60		-30...+50		-30...+60	
IP rating	IP24		IP24		IP24		IP24		IP24		IP24		IP24	
Motor IP rating	IP44		IP44		IP44		IP44		IP44		IP54		IP54	

**AXIS-F 200 2E**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
LWA to environment [dBA]	<b>68</b>	28	39	52	58	66	62	57	50	<b>48</b>	<b>58</b>




**AXIS-F 250 2E, AXIS-F 250 4E**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
LWA to environment [dBA]	<b>70</b>	29	40	54	60	68	64	59	52	<b>50</b>	<b>60</b>

Axis-F 250 2E											
LWA to environment [dBA]	<b>70</b>	29	40	54	60	68	64	59	52	<b>50</b>	<b>60</b>

Axis-F 250 4E											
LWA to environment [dBA]	<b>59</b>	25	39	43	49	54	54	49	43	<b>38</b>	<b>48</b>




**AXIS-F 300 2E, AXIS-F 300 4E**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
LWA to environment [dBA]	<b>74</b>	40	49	63	63	71	67	60	56	<b>53</b>	<b>63</b>

Axis-F 300 4E											
LWA to environment [dBA]	<b>64</b>	41	52	47	54	60	60	52	44	<b>44</b>	<b>54</b>

η [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR
30.5	A	Static	42.2	No	0.141	0.64	1380	110	2350	1




**AXIS-F 350 4E, AXIS-F 400 4E**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
LWA to environment [dBA]	<b>67</b>	26	43	49	60	62	62	53	46	<b>46</b>	<b>56</b>

Axis-F 400 4E											
LWA to environment [dBA]	<b>73</b>	46	52	58	65	68	68	65	57	<b>53</b>	<b>63</b>

η [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR
29.9	A	Static	41.8	No	0.130	0.6	1717	80	1375	1

Axis-F 400 4E											
LWA to environment [dBA]	<b>33.8</b>	A	Static	44.8	No	0.187	0.86	2787	80	1355	1





Parameters	Axis-F 450 4E	Axis-F 450 4E (220V/60Hz)	Axis-F 450 6E	Axis-F 450 6E (220V/60Hz)	Axis-F 500 4E	Axis-F 500 4E (220V/60Hz)	Axis-F 500 6E	Axis-F 500 6E (220V/60Hz)
Voltage [V]	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230
Frequency [Hz]	50	60	50	60	50	60	50	60
Power [W]	250	325	151	161	420	455	220	268
Current [A]	1.2	1.46	0.78	0.8	1.95	2.05	1.1	1.22
Maximum air flow [m³/h (l/s)]	4680 (1300)	4790 (1331)	3200 (889)	3250 (903)	7060 (1961)	7130 (1981)	4880 (1356)	5380 (1495)
RPM [min⁻¹]	1350	1600	945	1115	1300	1630	945	1105
Sound pressure at 3 m [dBA]	56	57	52	52	58	59	56	56
Transported air temperature [°C]	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50
IP rating	IP24	IP24	IP24	IP24	IP24	IP24	IP24	IP24
Motor IP rating	IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54

**AXIS-F 450 4E, AXIS-F 450 6E**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 450 4E</b>											
LWA to environment [dBA]	76	46	57	64	70	72	70	66	58	56	66
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
<b>Axis-F 450 4E</b>											
32.0	A	Static	41.8	No	0.288	1.31	3610	90	1270	1	
<b>Axis-F 450 6E</b>											
28.3	A	Static	37.2	No	0.139	0.7	1733	72	910	1	

**AXIS-F 500 4E, AXIS-F 500 6E**


Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 500 4E</b>											
LWA to environment [dBA]	79	49	60	67	73	74	73	68	60	58	68
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
<b>Axis-F 500 4E</b>											
32.1	A	Static	40.7	No	0.440	2.01	4987	100	1285	1	
<b>Axis-F 500 6E</b>											
30.1	A	Static	41.1	No	0.186	0.86	3288	60	900	1	




Parameters	Axis-F 550 4E	Axis-F 550 4E (220V/60Hz)	Axis-F 550 6E	Axis-F 550 6E (220V/60Hz)	Axis-F 630 4E	Axis-F 630 4E (220V/60Hz)	Axis-F 630 6E	Axis-F 630 6E (220V/60Hz)
Voltage [V]	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230	1 ~ 230
Frequency [Hz]	50	60	50	60	50	60	50	60
Power [W]	550	654	330	375	750	979	540	610
Current [A]	2.55	2.88	1.6	1.63	3.5	4.26	2.4	2.74
Maximum air flow [m³/h (l/s)]	8800 (2445)	8970 (2492)	6400 (1778)	6520 (1811)	11900 (3306)	12100 (3361)	10900 (3028)	10990 (3053)
RPM [min <sup>-1</sup> ]	1300	1580	950	1060	1360	1625	850	1075
Sound pressure at 3 m [dBA]	62	63	58	58	67	68	59	59
Transported air temperature [°C]	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50
IP rating	IP24	IP24	IP24	IP24	IP24	IP24	IP24	IP24
Motor IP rating	IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54

**AXIS-F 550 4E, AXIS-F 550 6E**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 550 4E</b>											
LWA to environment [dBA]	83	52	64	71	77	78	77	72	64	62	72
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
<b>Axis-F 550 4E</b>											
34.7	A	Static		No	0.581	2.64	5919	120	1240	1	
<b>Axis-F 550 6E</b>											
33.3	A	Static		No	0.279	1.34	4087	80	910	1	


**AXIS-F 630 4E, AXIS-F 630 6E**


Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 630 4E</b>											
LWA to environment [dBA]	88	57	68	76	81	83	82	77	69	67	77
<b>Axis-F 630 6E</b>											
LWA to environment [dBA]	80	51	62	69	74	75	73	67	59	59	69
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
<b>Axis-F 630 4E</b>											
37.5	A	Static		No	0.800	3.76	7095	149	1290	1	
<b>Axis-F 630 6E</b>											
35.0	A	Static		No	0.500	2.55	6857	90	915	1	



Parameters	Axis-F 250 2D		Axis-F 250 4D		Axis-F 300 2D		Axis-F 300 4D		Axis-F 350 4D		Axis-F 400 4D	
Voltage [V]	3 ~ 400		3 ~ 400		3 ~ 400		3 ~ 400		3 ~ 400		3 ~ 400	
Frequency [Hz]	50	60	50	60	50	60	50	60	50	60	50	60
Power [W]	80	92	60	89	145	165	75	94	140	150	180	195
Current [A]	0.22	0.24	0.17	0.22	0.25	0.29	0.22	0.25	0.38	0.46	0.47	0.55
Maximum air flow [m³/h (l/s)]	1060 (294)	1150 (319)	850 (236)	885 (246)	2310 (642)	2390 (664)	1310 (364)	1530 (425)	2350 (653)	2660 (739)	3740 (1039)	3870 (1075)
RPM [min⁻¹]	2600	3030	1400	1750	2350	2570	1380	1640	1419	1638	1380	1625
Sound pressure at 3 m [dBA]	51	52	38	38	52	52	45	45	46	46	54	54
Transported air temperature [°C]	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50
IP rating	IP24		IP24		IP24		IP24		IP24		IP24	
Motor IP rating	IP44		IP44		IP44		IP44		IP54		IP54	


**AXIS-F 250 2D, AXIS-F 250 4D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 250 2D</b>											
LWA to environment [dBA]	71	29	41	55	61	69	65	60	52	51	61
<b>Axis-F 250 4D</b>											
LWA to environment [dBA]	59	25	39	43	49	54	54	49	43	38	48




**AXIS-F 300 2D, AXIS-F 300 4D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 300 2D</b>											
LWA to environment [dBA]	73	39	48	62	62	70	66	60	55	52	62
<b>Axis-F 300 4D</b>											
LWA to environment [dBA]	65	42	53	46	55	61	61	53	44	45	55
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
30.3	A	Static		No	0.141	0.25	1367	110	2350	1	



**AXIS-F 350 4D, AXIS-F 400 4D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 350 4D</b>											
LWA to environment [dBA]	66	26	43	48	59	62	62	53	46	46	56
<b>Axis-F 400 4D</b>											
LWA to environment [dBA]	74	31	48	58	63	70	70	66	58	54	64
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
31.7	A	Static	43.7	No	0.129	0.37	1802	80	1400	1	
<b>Axis-F 400 4D</b>											
34.3	A	Static	44.9	No	0.209	0.47	2807	90	1365	1	





Parameters	Axis-F 450 4D	Axis-F 450 4D (220V/60Hz)	Axis-F 450 6D	Axis-F 450 6D (220V/60Hz)	Axis-F 500 4D	Axis-F 500 4D (220V/60Hz)	Axis-F 500 6D	Axis-F 500 6D (220V/60Hz)
Voltage [V]	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400
Frequency [Hz]	50	60	50	60	50	60	50	60
Power [W]	250	275	148	175	450	370	230	281
Current [A]	0.6	0.65	0.42	0.47	0.9	0.7	0.58	0.59
Maximum air flow [m <sup>3</sup> /h (l/s)]	5280 (1467)	5350 (1486)	3500 (972)	3580 (995)	6570 (1825)	6230 (1731)	4900 (1361)	5430 (1508)
RPM [min <sup>-1</sup> ]	1360	1620	900	1050	1300	1605	920	1015
Sound pressure at 3 m [dBA]	56	56	53	53	60	60	57	57
Transported air temperature [°C]	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50
IP rating	IP24	IP24	IP24	IP24	IP24	IP24	IP24	IP24
Motor IP rating	IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54

**AXIS-F 450 4D, AXIS-F 450 6D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 450 4D</b>											
L <sub>WA</sub> to environment [dBA]	77	48	60	67	70	71	72	67	59	56	66
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m <sup>3</sup> /h]	[Pa]	[RPM]	SR	
<b>Axis-F 450 4D</b>											
35.1	A	Static		44.8	No	0.296	0.59	3659	100	1310	1
<b>Axis-F 450 6D</b>											
28.4	A	Static		37.9	No	0.145	0.4	1790	75	900	1

**AXIS-F 500 4D, AXIS-F 500 6D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 500 4D</b>											
L <sub>WA</sub> to environment [dBA]	81	51	63	70	74	75	76	71	62	60	70
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m <sup>3</sup> /h]	[Pa]	[RPM]	SR	
<b>Axis-F 500 4D</b>											
35.5	A	Static		43.9	No	0.478	0.9	4988	120	1305	1
<b>Axis-F 500 6D</b>											
30.5	A	Static		41.5	No	0.185	0.47	3308	60	915	1





Parameters	Axis-F 550 4D	Axis-F 550 4D (220V/60Hz)	Axis-F 550 6D	Axis-F 550 6D (220V/60Hz)	Axis-F 630 4D	Axis-F 630 4D (220V/60Hz)	Axis-F 630 6D	Axis-F 630 6D (220V/60Hz)
Voltage [V]	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400	3 ~ 400
Frequency [Hz]	50	60	50	60	50	60	50	60
Power [W]	750	600	337	447	800	910	550	716
Current [A]	1.5	1.1	0.9	0.95	1.6	1.68	1.45	1.56
Maximum air flow [m³/h (l/s)]	9700 (2695)	7380 (2050)	6400 (1778)	6520 (1811)	12200 (3389)	12400 (3445)	10950 (3042)	11120 (3089)
RPM [min⁻¹]	1350	1605	910	1020	1320	1585	900	1060
Sound pressure at 3 m [dBA]	64	64	61	61	69	69	72	73
Transported air temperature [°C]	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50	-30...+60	-30...+50
IP rating	IP24	IP24	IP24	IP24	IP24	IP24	IP24	IP24
Motor IP rating	IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54

**AXIS-F 550 4D, AXIS-F 550 6D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA	
		63	125	250	500	1000	2000	4000	8000	3 m	1 m
<b>Axis-F 550 4D</b>											
LWA to environment [dBA]	85	53	65	72	79	80	79	73	65	64	74
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
<b>Axis-F 550 4D</b>											
38.8	A	Static	46.3	No	0.656	1.27	6400	140	1175	1	
<b>Axis-F 550 6D</b>											
34.4	A	Static	44.3	No	0.273	0.74	4142	80	920	1	

**AXIS-F 630 4D, AXIS-F 630 6D**


Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA	
		63	125	250	500	1000	2000	4000	8000	3 m	1 m
<b>Axis-F 630 4D</b>											
LWA to environment [dBA]	90	58	69	78	83	85	84	79	70	69	79
$\eta$ [%]	MC	EC	N	VSD	[kW]	[A]	[m³/h]	[Pa]	[RPM]	SR	
<b>Axis-F 630 4D</b>											
41.2	A	Static	48.1	No	0.810	1.61	7743	152	1290	1	
<b>Axis-F 630 6D</b>											
37.0	A	Static	45.2	No	0.515	1.33	6737	100	920	1	



Parameters	Axis-F 710 6D	Axis-F 710 8D	Axis-F 800 8D
Voltage [V]	3 ~ 400	3 ~ 400	3 ~ 400
Frequency [Hz]	50	50	50
Power [W]	1150	700	700
Current [A]	2.0	1.5	1.7
Maximum air flow [m <sup>3</sup> /h (l/s)]	15440 (4289)	12000 (3334)	15550 (4320)
RPM [min <sup>-1</sup> ]	830	710	710
Sound pressure at 3 m [dBA]	63	61	66
Transported air temperature [°C]	-30...+60	-30...+60	-30...+60
IP rating	IP24	IP24	IP24
Motor IP rating	IP54	IP54	IP54

**AXIS-F 710 6D, AXIS-F 710 8D**

Sound power level, A-weighted	Total	Octave frequency bands [Hz]								LpA 3 m	LpA 1 m
		63	125	250	500	1000	2000	4000	8000		
<b>Axis-F 710 6D</b>											
L <sub>WA</sub> to environment [dBA]	83	54	65	72	78	79	77	70	62	63	73
η [%]	MC	EC	N	VSD	[kW]	[A]	[m <sup>3</sup> /h]	[Pa]	[RPM]	SR	
<b>Axis-F 710 6D</b>											
35.6	A	Static	42	No	0.979	1.91	8777	140	830	1	
<b>Axis-F 710 8D</b>											
29.4	A	Static	37	No	0.648	1.48	8110	83	810	1	


**AXIS-F 800 8D**

η [%]	MC	EC	N	VSD	[kW]	[A]	[m <sup>3</sup> /h]	[Pa]	[RPM]	SR
32.2	A	Static	39.5	No	0.695	1.7	10955	72	710	1

