

| | | | | | | |
|---|----------------------|----|---------|---|-------|---|
| Trade mark | BLAUBERG | | | | | |
| Model | Iso-Mix 200 | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .a) | Cold | | Average | | Warm | |
| | -52,8 | A+ | -25,7 | C | -10,2 | E |
| Type of ventilation unit | Unidirectional | | | | | |
| Type of drive installed | Multi-speed | | | | | |
| Type of heat recovery system | None | | | | | |
| Thermal efficiency of heat recovery, % | N/A | | | | | |
| Maximum flow rate, m ³ /h | 800 | | | | | |
| Electric power input, W | 110 | | | | | |
| Sound power level, dB(A) | 33 | | | | | |
| Reference flow rate, m ³ /s | 0,156 | | | | | |
| Reference pressure difference, Pa | 50 | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,139 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | N/A | | | | | |
| Maximum external leakage rates, % | 2,7 | | | | | |
| Internet address | | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Cold | | Average | | Warm | |
| | 104 | | 104 | | 104 | |
| The annual heating saved (AHS), kWh primary energy/a | Cold | | Average | | Warm | |
| | 5 536 | | 2 830 | | 1 280 | |