

| | | | | | | |
|---|---|----|---------|---|-------|---|
| Trade mark | BLAUBERG | | | | | |
| Model | KOMFORT Roto EC LE400-2 S18 | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .a) | Cold | | Average | | Warm | |
| | -78,1 | A+ | -39,6 | A | -14,9 | E |
| Type of ventilation unit | Bidirectional | | | | | |
| Type of drive installed | Multi-speed | | | | | |
| Type of heat recovery system | Regenerative | | | | | |
| Thermal efficiency of heat recovery, % | 85 | | | | | |
| Maximum flow rate, m ³ /h | 400 | | | | | |
| Electric power input, W | 200 | | | | | |
| Sound power level, dB(A) | 65 | | | | | |
| Reference flow rate, m ³ /s | 0,078 | | | | | |
| Reference pressure difference, Pa | 50 | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,357 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | 2,7 | | | | | |
| Maximum external leakage rates, % | 2,7 | | | | | |
| Internet address | http://www.blaubergventilatoren.de/ | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Cold | | Average | | Warm | |
| | 816 | | 279 | | 234 | |
| The annual heating saved (AHS), kWh primary energy/a | Cold | | Average | | Warm | |
| | 8 979 | | 4 590 | | 2 075 | |