

EXTERNAL CONTROLLERS

MOUNTING BOXES



MKV-6. ROUND MOUNTING BOX

Recessed box for use in masonry with an installation depth of at least 66 mm.

- 4×3 screw caps.
- 2 pre-installed screws for devices.
- Connector with a bayonet lock that connects on both sides.
- 6 combined inlets for pipes Ø 20 and 25 mm.
- 4 Ø 20 mm inlets.
- 2 Ø 14 mm inlets.
- 1 inlet Ø 20 mm at the base.

Tested according to DIN EN 60670-1, DIN EN 60670-22 and DIN 49073-1.



MKV-7. ROUND MOUNTING BOX WITH EXTRA SPACE UE 66 FOR BRICK WALLS

- Length: 61 mm
- Width: 66 mm
- Material: polypropylene/thermoplastic elastomer
- Fire resistance: 650 °C



MKV-8. ROUND MOUNTING BOX WITH ADDITIONAL SPACE UE 66-L FOR BRICK WALLS, WITH MEMBRANES

- Length: 61 mm
- Width: 66 mm
- Material: polypropylene/thermoplastic elastomer
- Fire resistance: 650 °C



MKV-9. ROUND MOUNTING BOX WITH EXTRA SPACE HE 74-L FOR HOLLOW WALLS

- Height: 154 mm
- Width: 71 mm
- Depth: 77 mm
- Material: polypropylene
- Fire resistance: 850 °C