



## Aero Still 125 S

Extract fan for low-noise applications

- Maximum airflow: 158
- Sound pressure level LpA at 3 m: 31
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord

|                                 | Unit of measurement | Aero Still 125 S |
|---------------------------------|---------------------|------------------|
| Connected air duct size         | mm                  | 125              |
| Speed                           | -                   | 1                |
| Minimum supply voltage          | V                   | 220              |
| Maximum supply voltage          | V                   | 240              |
| Power supply frequency          | Hz                  | 50               |
| Rated power                     | W                   | 9.4              |
| Unit current                    | A                   | 0.059            |
| Maximum airflow                 | m <sup>3</sup> /h   | 158              |
| Sound pressure level LpA at 3 m | dB(A)               | 31               |
| Ambient air temperature min     | °C                  | 1                |
| Ambient air temperature max     | °C                  | 40               |
| Ingress protection rating       | -                   | IP34             |

### Dimensions

| a   | b   | c  | Ø d | e  |
|-----|-----|----|-----|----|
| 168 | 144 | 97 | 125 | 30 |




## Ecodesign



|   |                  |   |         |   |      |   |
|---|------------------|---|---------|---|------|---|
| Trademark   | Blauberg         |   |         |   |      |   |
| Model   | Aero Still 125 S |   |         |   |      |   |
| Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a)) | Cold             |   | Average |   | Warm |   |
|   | 0                | B | 0       | E | 0    | F |
| Type of ventilation unit                                    | Unidirectional   |   |         |   |      |   |
| Type of drive installed                                     | Multi-speed      |   |         |   |      |   |
| Type of heat recovery system                                | None             |   |         |   |      |   |
| Maximum flow rate (m <sup>3</sup> /h)                       | 0                |   |         |   |      |   |
| Electric power input (W)                                    | 0                |   |         |   |      |   |
| Reference flow rate (m <sup>3</sup> /s)                     | 0                |   |         |   |      |   |
| Specific power input (SPI) (W/(m <sup>3</sup> /h))          | 0                |   |         |   |      |   |
| Control typology  | Manual control   |   |         |   |      |   |
| Maximum external leakage rates (%)                          | 0                |   |         |   |      |   |
| Sound power level (dB(A))                                   | 0                |   |         |   |      |   |
| Declared typology   | RVU UVU          |   |         |   |      |   |
| The annual heating saved (AHS) (kWh/a)                      | Cold             |   | Average |   | Warm |   |
|   | 0                |   | 0       |   | 0    |   |

## Accessories

### Thyristor speed controllers

| Name                     | Photo   | Description                |
|--------------------------|---|----------------------------|
| <a href="#">CDT E1.8</a> |  | Thyristor speed controller |