



# Aero Still Chrome 125 T

Extract fan for low-noise applications

- Maximum airflow: 158
- Sound pressure level LpA at 3 m: 31
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Timer: Turn off timer

|                                 | Unit of measurement | Aero Still Chrome 125 T |
|---------------------------------|---------------------|-------------------------|
| Connected air duct size         | mm                  | 125                     |
| Speed                           | -                   | 1                       |
| Minimum supply voltage          | V                   | 220                     |
| Maximum supply voltage          | V                   | 240                     |
| Power supply frequency          | Hz                  | 50                      |
| Rated power                     | W                   | 9.4                     |
| Unit current                    | A                   | 0.059                   |
| Maximum airflow                 | m <sup>3</sup> /h   | 158                     |
| Sound pressure level LpA at 3 m | dB(A)               | 31                      |
| Ambient air temperature min     | °C                  | 1                       |
| Ambient air temperature max     | °C                  | 40                      |
| Ingress protection rating       | -                   | IP34                    |

## Dimensions

| a   | b   | c  | Ø d | e  |
|-----|-----|----|-----|----|
| 168 | 144 | 97 | 125 | 30 |



## Accessories

### Other accessories

| Name                     | Photo  | Description                |
|--------------------------|--|----------------------------|
| <a href="#">CDT E1.8</a> |  | Thyristor speed controller |