



# Aero Vintage 150 ST

Low-noise axial fan for exhaust ventilation

- Maximum airflow: 309
- Sound pressure level LpA at 3 m: 40
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord
- Timer: Turn off timer

|                                 | Unit of measurement | Aero Vintage 150 ST |
|---------------------------------|---------------------|---------------------|
| Connected air duct size         | mm                  | 150                 |
| Speed                           | -                   | 1                   |
| Minimum supply voltage          | V                   | 220                 |
| Maximum supply voltage          | V                   | 240                 |
| Power supply frequency          | Hz                  | 50                  |
| Rated power                     | W                   | 24                  |
| Unit current                    | A                   | 0.13                |
| Maximum airflow                 | m <sup>3</sup> /h   | 309                 |
| rotation speed at 50hz          | -                   | 2400                |
| Sound pressure level LpA at 3 m | dB(A)               | 40                  |
| Weight                          | kg                  | 0.9                 |
| Ambient air temperature min     | °C                  | 1                   |
| Ambient air temperature max     | °C                  | 45                  |
| Ingress protection rating       | -                   | IP34                |

## Dimensions

| a   | b   | c   | Ø d | e  |
|-----|-----|-----|-----|----|
| 198 | 170 | 119 | 150 | 30 |



## Ecodesign



|   |                     |   |         |   |      |   |
|---|---------------------|---|---------|---|------|---|
| Trademark   | Blauberg            |   |         |   |      |   |
| Model   | Aero Vintage 150 ST |   |         |   |      |   |
| Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a)) | Cold                |   | Average |   | Warm |   |
|   | 0                   | B | 0       | E | 0    | F |
| Type of ventilation unit                                    | Unidirectional      |   |         |   |      |   |
| Type of drive installed                                     | Multi-speed         |   |         |   |      |   |
| Type of heat recovery system                                | None                |   |         |   |      |   |
| Maximum flow rate (m <sup>3</sup> /h)                       | 0                   |   |         |   |      |   |
| Electric power input (W)                                    | 0                   |   |         |   |      |   |
| Reference flow rate (m <sup>3</sup> /s)                     | 0                   |   |         |   |      |   |
| Specific power input (SPI) (W/(m <sup>3</sup> /h))          | 0                   |   |         |   |      |   |
| Control typology  | Manual control      |   |         |   |      |   |
| Maximum external leakage rates (%)                          | 0                   |   |         |   |      |   |
| Sound power level (dB(A))                                   | 0                   |   |         |   |      |   |
| Declared typology   | RVU UVU             |   |         |   |      |   |
| The annual electricity consumption (AEC) (kWh/a)            | Cold                |   | Average |   | Warm |   |
|   | 0                   |   | 0       |   | 0    |   |
| The annual heating saved (AHS) (kWh/a)                      | Cold                |   | Average |   | Warm |   |
|   | 0                   |   | 0       |   | 0    |   |