



Axis-QR 450 4E

Wall-mounted axial fans



- Sound pressure level LpA at 3 m: 56
- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	Axis-QR 450 4E
Connected air duct size	mm	450
Phases	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	250
Unit current	A	1.2
Maximum airflow	m ³ /h	4680
Rotation speed at 50hz	-	1350
Sound pressure level LpA at 3 m	dB(A)	56
Weight	kg	10
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IP24
Ingress protection rating of the drive	-	IP54
Impeller material	-	Coated steel
Article	-	8013591



Dimensions

ØD	ØD1	ØD2	Ød	L
465	578	607	11	230



Ecodesign

Trademark	Blauberg
Model	Axis-QR 450 4E
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	90
Maximum external leakage rates (%)	2.7
Static efficiency (%)	32
Declared typology	NRVU UVU
Effective electric power input (kW)	0.288
Sound power level (dB(A))	84