

BL01 CFV 800

Floor mounted heat recovery units

- Sound pressure level LpA at 3 m: 30
- Heat exchanger type: Plate counterflow
- Heat exchanger material: Profiled polystyrene plates
- Supply filter: ePM1 70% (ISO 16890)-F7 (EN779)
- Extract filter: ePM10 55% (ISO 16890)-M5 (EN779)
- Sound-insulated casing
- Bypass: Auto
- Reheater: Optional
- Preheater: Optional
- BMS protocol: Bacnet, ModBus
- Control: Wired control panel
- Casing material: Aluzinc steel

	Unit of measurement	BL01 CFV 800
Casing performance	-	40 mm, T3/TB4
Connected air duct size	mm	315
Phases	-	1
Minimum supply voltage	V	200
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power supply fan	W	168
Rated power extract fan	W	168
Unit current (without electric heaters)	A	2.75
Maximum airflow	m³/h	1000
Maximum airflow at ESP 200 Pa	m³/h	900
Sound pressure level LpA at 3 m	dB(A)	30
Heat exchanger type	-	Plate counterflow
Heat exchanger material	-	Profiled polystyrene plates
Weight	kg	200
Supply filter	-	ePM1 70% (ISO 16890)-F7 (EN779)
Extract filter	-	ePM10 55% (ISO 16890)-M5 (EN779)
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ambient air temperature max	°C	60
Ambient air temperature min	°C	-40

Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP54

Dimensions