

# BlauAIR CFP 1200

Ceiling mounted heat recovery units



- Maximum airflow: 1200
- Sound pressure level LpA at 3 m: 35
- Heat exchanger type: Counter flow
- Extract filter: ePM1 55% (ISO 16890)-F7 (EN779)
- Supply filter: ePM1 55% (ISO 16890)-F7 (EN779)
- Sound insulation
- Motor type: EC
- Bypass: Auto
- Reheater: Optional
- Preheater: Optional
- BMS protocol: Bacnet
- Control: Wired control panel
- Casing material: Aluzinc steel

	Unit of measurement	BlauAIR CFP 1200	
Connected air duct size	mm	500x300	
Speed	-	1	
Phases	-	1	
Minimum supply voltage	V	200	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50/60	
Rated power	W	460	
Unit current	A	4	6
Maximum airflow	m <sup>3</sup> /h	1200	
Sound pressure level LpA at 3 m	dB(A)	35	
Heat exchanger type	-	Counter flow	
Heat exchanger material	-	Aluminum	
Weight	kg	120	
Extract filter	-	ePM1 55% (ISO 16890)-F7 (EN779)	
Supply filter	-	ePM1 55% (ISO 16890)-F7 (EN779)	
Transported air temperature (max)	°C	40	
Transported air temperature (min)	°C	-25	
Ambient air temperature min	°C	-35	
Ambient air temperature max	°C	50	
Ingress protection rating	-	IP34	

Ingress protection rating of the drive	-	IP54
--	---	------

## Dimensions

L	W	H	H1	S1
1800	1440	380	250	500

