




BLAUBOX DE 2500-18 Pro

Supply suspended ventilation units


- Power of electrical reheater: 18000
- Maximum airflow: 2500
- Sound pressure level LpA at 3 m: 54
- Sound insulation
- Motor type: AC
- Reheater: Electric
- Control: Remote Control
- Casing material: Galvanized steel

	Unit of measurement	BLAUBOX DE 2500-18 Pro
Connected air duct size	mm	500x300
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	620
Power of electrical reheater	W	18000
Unit current	A	27.1
Maximum airflow	m ³ /h	2500
Sound pressure level LpA at 3 m	dB(A)	54
Weight	kg	61
Transported air temperature (max)	°C	45
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	-25
Ambient air temperature max	°C	45
Ambient air humidity max	%	80
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP44




Dimensions

B	B1	B2	B3	H	H1	H2	L	L1
500	520	689	646	300	320	447	1250	1212




Accessories



Other accessories

Name	Photo	Description
FP 442x275x47 G4		G4 panel filter



Other accessories

Name	Photo	Description
SD 50x30		Silencers for rectangular ducts

Other accessories

Name	Photo	Description
KFK 50x30-3		Duct DX cooling units for rectangular air ducts
KWK 50x30-3		Duct water cooling units for rectangular air ducts

Other accessories

Name	Photo	Description
SL 50x30		Air dampers for rectangular ducts
EVA 50x30		Flexible anti-vibration connectors for rectangular ducts