




Box 100x50 4D

Centrifugal fans for rectangular ducts




- Maximum airflow: 15000
- Sound pressure level LpA at 3 m: 70
- Motor type: AC
- Impeller type: Centrifugal backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	Box 100x50 4D
Connected air duct size	mm	1000x500
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	4300
Unit current	A	6.8
Maximum airflow	m ³ /h	15000
Sound pressure level LpA at 3 m	dB(A)	70
Weight	kg	126
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44



Dimensions

B	B1	H	H1	H2	L
1000	1040	500	540	720	1150



Ecodesign

Trademark	Blauberg
Model	Box 100x50 4D
Type of ventilation unit	Unidirectional
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	2.294
Nominal external pressure (Pa)	880
Maximum external leakage rates (%)	2.7
Static efficiency (%)	55.5
Declared typology	NRVU UVU
Sound power level (dB(A))	90
Effective electric power input (kW)	3.71

Accessories

Other accessories

Name	Photo	Description
CDT E1.8		Thyristor speed controller