



Bravo 100

Extract fans

- Maximum airflow: 101
- Sound pressure level LpA at 3 m: 35
- Motor type: AC

	Unit of measurement	Bravo 100
Connected air duct size	mm	100
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	14
Unit current	A	0.085
Maximum airflow	m ³ /h	101
Sound pressure level LpA at 3 m	dB(A)	35
Ingress protection rating	-	IP34

Dimensions

a	b	c	∅ d	e
150	122	102	100	17




Ecodesign



Trademark	Blauberg					
Model	Bravo 100					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-31	B	-14	E	-5	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	101					
Electric power input (W)	14					
Reference flow rate (m ³ /s)	0.02					
Specific power input (SPI) (W/(m ³ /h))	0.089					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	55					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average		Warm		
	100	100		100		
The annual heating saved (AHS) (kWh/a)	Cold	Average		Warm		
	3400	1700		800		

Accessories

Thyristor speed controllers
















Name	Photo	Description
CDT E1.8		Thyristor speed controller














Flexible ducts

Name	Photo	Description
BlauFlex PVC		Flexible air ducts BlauFlex

Flat duct

Name	Photo	Description
------	-------	-------------

BlauPlast RR 100/0.5		Round duct
BlauPlast RR 100/1		Round duct
BlauPlast RR 100/1.5		Round duct
BlauPlast RTR 100/0.35-0.5		Round telescopic duct
BlauPlast RTR 100/0.5-1		Round telescopic duct
BlauPlast RV 100		Round duct connector
BlauPlast RSV 100		Flexible duct connector
BlauPlast RB 100/90°		Bend 90°
BlauPlast RH 100		Round duct holder
BlauPlast RVP 100		Round duct connector with plate
BlauPlast RVPK 100		Round duct connector with a plate and a gravity backdraft damper
BlauPlast US-90° 100/110x55		Bend
BlauPlast US-90° 100/204x60		Bend
BlauPlast UBS 100/110x55		Connector
BlauPlast FRT 100/110x55		Flat to round connector

BlauPlast RR 100/0.35		Round duct
BlauPlast RR 100/2		Round duct
BlauPlast RR 100/2.5		Round duct
BlauPlast RVK 100		Connector with backdraft damper for round ducts
BlauPlast RB 100/45°		Bend 45°
BlauPlast WP 100		Wall plate for round ducts
BlauPlast RVF 100		Round flexible duct connector
BlauPlast RVF 100 R		Round flexible duct connector
BlauPlast RVFI 100		Round flexible duct connector
BlauPlast RVFI 100 R		Round flexible duct connector
BlauPlast RRT 100		T-joint for round ducts
BlauPlast US 100/110x55		Reducer for flat and round ducts
BlauPlast USV 100/110x55		Reducer for flat and round ducts