



Bravo 100 ST

Extract fans

- Maximum airflow: 101
- Sound pressure level LpA at 3 m: 35
- Motor type: AC
- Pull cord
- Timer: Turn off timer

	Unit of measurement	Bravo 100 ST
Connected air duct size	mm	100
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	14
Unit current	A	0.085
Maximum airflow	m ³ /h	101
Sound pressure level LpA at 3 m	dB(A)	35
Ingress protection rating	-	IP34

Dimensions

a	b	c	∅ d	e
150	122	102	100	17



Ecodesign



Trademark	Blauberg					
Model	Bravo 100 ST					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-31	B	-14	E	-5	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	101					
Electric power input (W)	14					
Reference flow rate (m ³ /s)	0.02					
Specific power input (SPI) (W/(m ³ /h))	0.089					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Sound power level (dB(A))	55					
Declared typology	RVU UVU					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average		Warm		
	100	100		100		
The annual heating saved (AHS) (kWh/a)	Cold	Average		Warm		
	3400	1700		800		