



## Bravo 125 T

Extract fans

- Maximum airflow: 192
- Sound pressure level LpA at 3 m: 37
- Motor type: AC
- Backdraft protection: Backdraft damper
- Timer: Turn off timer

	Unit of measurement	Bravo 125 T
Connected air duct size	mm	125
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	16
Unit current	A	0.1
Maximum airflow	m <sup>3</sup> /h	192
Sound pressure level LpA at 3 m	dB(A)	37
Ingress protection rating	-	IP34

### Dimensions

a	b	c	∅ d	e
176	144	104	125	17



## Ecodesign



Trademark	Blauberg					
Model	Bravo 125 T					
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold		Average		Warm	
	-35.1	A	-17.2	E	-6.9	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m <sup>3</sup> /h)	192					
Electric power input (W)	16					
Reference flow rate (m <sup>3</sup> /s)	0.037					
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.054					
Control typology	Clock control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	57					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average		Warm		
	62	62		62		
The annual heating saved (AHS) (kWh/a)	Cold	Average		Warm		
	3667	1874		848		