



# Bravo 150

Extract fans

- Maximum airflow: 305
- Sound pressure level LpA at 3 m: 39
- Motor type: AC
- Backdraft protection: Backdraft damper

	Unit of measurement	Bravo 150
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	24
Unit current	A	0.13
Maximum airflow	m <sup>3</sup> /h	305
Sound pressure level LpA at 3 m	dB(A)	39
Ingress protection rating	-	IP34

## Dimensions

a	b	c	∅ d	e
205	174	124	150	19



## Ecodesign



Trademark	Blauberg					
Model	Bravo 150					
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold		Average		Warm	
	-32	B	-16	E	-6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m <sup>3</sup> /h)	305					
Electric power input (W)	24					
Reference flow rate (m <sup>3</sup> /s)	0.059					
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.051					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	59					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	100		100		100	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3400		1700		800	


## Accessories

### Thyristor speed controllers













Name	Photo	Description
<a href="#">CDT E1.8</a>		Thyristor speed controller









### Flexible ducts

Name	Photo	Description
<a href="#">BlauFlex PVC</a>		Flexible air ducts BlauFlex

<a href="#">BlauFlex Iso N 152/7.6</a>		Flexible air ducts BlauFlex
--	---	-----------------------------

## Flat duct

Name	Photo	Description
<a href="#">BlauPlast RR 150/0.5</a>		Round duct
<a href="#">BlauPlast RR 150/1</a>		Round duct
<a href="#">BlauPlast RR 150/1.5</a>		Round duct
<a href="#">BlauPlast RTR 150/0.35-0.5</a>		Round telescopic duct
<a href="#">BlauPlast RTR 150/0.5-1</a>		Round telescopic duct
<a href="#">BlauPlast RV 150</a>		Round duct connector
<a href="#">BlauPlast RSV 150</a>		Flexible duct connector
<a href="#">BlauPlast RB 150/90°</a>		Bend 90°
<a href="#">BlauPlast RH 150</a>		Round duct holder
<a href="#">BlauPlast RVP 150</a>		Round duct connector with plate
<a href="#">BlauPlast RVPK 150</a>		Round duct connector with a plate and a gravity backdraft damper
<a href="#">BlauPlast RR 150/0.35</a>		Round duct

<a href="#">BlauPlast RR 150/2</a>		Round duct
<a href="#">BlauPlast RR 150/2.5</a>		Round duct
<a href="#">BlauPlast RVK 150</a>		Connector with backdraft damper for round ducts
<a href="#">BlauPlast WP 150</a>		Wall plate for round ducts
<a href="#">BlauPlast RRT 150</a>		T-joint for round ducts
<a href="#">BlauPlast US-90° 150/204x60</a>		Bend
<a href="#">BlauPlast US-90° 150/220x90</a>		Bend
<a href="#">BlauPlast UBS 150/220x90</a>		Connector