



Bravo 150 T

Extract fans

- Maximum airflow: 305
- Sound pressure level LpA at 3 m: 39
- Motor type: AC
- Backdraft protection: Backdraft damper
- Timer: Turn off timer

	Unit of measurement	Bravo 150 T
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	24
Unit current	A	0.13
Maximum airflow	m ³ /h	305
Sound pressure level LpA at 3 m	dB(A)	39
Ingress protection rating	-	IP34

Dimensions

a	b	c	∅ d	e
205	174	124	150	19



Ecodesign



Trademark	Blauberg					
Model	Bravo 150 T					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-35.2	A	-17.3	E	-7	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	305					
Electric power input (W)	24					
Reference flow rate (m ³ /s)	0.059					
Specific power input (SPI) (W/(m ³ /h))	0.051					
Control typology	Clock control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	59					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	59		59		59	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3667		1874		848	