



Bravo Platinum 125

Extract fans

- Maximum airflow: 192
- Sound pressure level LpA at 3 m: 37
- Motor type: AC
- Backdraft protection: Backdraft damper

	Unit of measurement	Bravo Platinum 125
Connected air duct size	mm	125
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	16
Unit current	A	0.1
Maximum airflow	m ³ /h	192
Sound pressure level LpA at 3 m	dB(A)	37
Ingress protection rating	-	IP34

Dimensions

a	b	c	∅ d	e
176	144	104	125	17

























Accessories

Other accessories

Name	Photo	Description
CDT E1.8		Thyristor speed controller

Air distribution

Name	Photo	Description
BlauFlex PVC		Flexible air ducts BlauFlex
BlauFlex Iso N 127/7.6		Flexible air ducts BlauFlex
BlauPlast RR 125/0.5		Round duct
BlauPlast RR 125/1		Round duct
BlauPlast RR 125/1.5		Round duct
BlauPlast RTR 125/0.35-0.5		Round telescopic duct
BlauPlast RTR 125/0.5-1		Round telescopic duct
BlauPlast RV 125		Round duct connector
BlauPlast RSV 125		Flexible duct connector

BlauPlast RB 125/90°		Bend 90°
BlauPlast RH 125		Round duct holder
BlauPlast RVP 125		Round duct connector with plate
BlauPlast RVPK 125		Round duct connector with a plate and a gravity backdraft damper
BlauPlast US-90° 125/204x60		Bend
BlauPlast UBS 125/204x60		Connector
BlauPlast RR 125/0.35		Round duct
BlauPlast RR 125/2		Round duct
BlauPlast RR 125/2.5		Round duct
BlauPlast RVK 125		Connector with backdraft damper for round ducts
BlauPlast RB 125/45°		Bend 45°
BlauPlast WP 125		Wall plate for round ducts
BlauPlast RRT 125		T-joint for round ducts
BlauPlast US-90° 125/220x90		Bend