



# Bravo Still Chrome 100 ST

Extract fans

- Maximum airflow: 70
- Sound pressure level LpA at 3 m: 26
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord
- Timer: Turn off timer

|                                 | Unit of measurement | Bravo Still Chrome 100 ST |
|---------------------------------|---------------------|---------------------------|
| Connected air duct size         | mm                  | 100                       |
| Speed                           | -                   | 1                         |
| Minimum supply voltage          | V                   | 220                       |
| Maximum supply voltage          | V                   | 240                       |
| Power supply frequency          | Hz                  | 50                        |
| Rated power                     | W                   | 5.6                       |
| Unit current                    | A                   | 0.04                      |
| Maximum airflow                 | m <sup>3</sup> /h   | 70                        |
| Sound pressure level LpA at 3 m | dB(A)               | 26                        |
| Ambient air temperature min     | °C                  | 1                         |
| Ambient air temperature max     | °C                  | 40                        |
| Ingress protection rating       | -                   | IP34                      |

## Dimensions

| a   | b   | c   | Ø d | e  |
|-----|-----|-----|-----|----|
| 150 | 122 | 102 | 100 | 17 |



## Accessories

### Thyristor speed controllers

| Name                     | Photo   | Description                |
|--------------------------|---|----------------------------|
| <a href="#">CDT E1.8</a> |  | Thyristor speed controller |