



Bravo Still Chrome 150 ST

Extract fans

- Maximum airflow: 235
- Sound pressure level LpA at 3 m: 35
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord
- Timer: Turn off timer

| | Unit of measurement | Bravo Still Chrome 150 ST |
|---------------------------------|---------------------|---------------------------|
| Connected air duct size | mm | 150 |
| Speed | - | 1 |
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 20 |
| Unit current | A | 0.13 |
| Maximum airflow | m ³ /h | 235 |
| Sound pressure level LpA at 3 m | dB(A) | 35 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 40 |
| Ingress protection rating | - | IP34 |

Dimensions

| a | b | c | ∅ d | e |
|-----|-----|-----|-----|----|
| 205 | 174 | 124 | 150 | 19 |



Accessories

Thyristor speed controllers

| Name | Photo | Description |
|--------------------------|---|----------------------------|
| CDT E1.8 |  | Thyristor speed controller |