





Centro-MZ 100 L

Centrifugal inline fans in galvanized casings

- Maximum airflow: 230
- Sound pressure level LpA at 3 m: 35
- Motor type: AC
- Impeller type: Centrifugal impeller with backward curved blades
- Casing material: Galvanized steel
- Installation in any position

	Unit of measurement	Centro-MZ 100 L
Connected air duct size	mm	100
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Rated power	W	42
Unit current	A	0.19
Maximum airflow	m ³ /h	230
Sound pressure level LpA at 3 m	dB(A)	35
Weight	kg	2.5
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44






Dimensions

ØD	ØD1	B	B1	L	L1	L2	L3
98	245	300	260	195	20	20	30



Ecodesign



Trademark	Blauberg					
Model	Centro-MZ 100 L					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-52.2	A+	-25.1	C	-9.6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	170					
Electric power input (W)	41					
Reference flow rate (m ³ /s)	0.033					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m ³ /h))	0.241					
Control typology	Local demand control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	35					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	128		128		128	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	5536		2830		1280	

Accessories

Thyristor speed controllers

Name	Photo	Description
CDT E1.8		Thyristor speed controller