



## Freshpoint 160-E Pro L07

Smart HRV unit for single-room ventilation with air filtration, an electric heater, customizable air flow settings and a user-friendly interface

- Power of electrical preheater: 100
- Maximum airflow: 57
- Sound pressure level LpA at 3 m: 42
- Heat recovery efficiency: 88
- Filter: G3
- Motor type: EC
- Preheater: Electric
- Control: Remote Control
- Casing material: Plastic
- Humidity sensor
- CO2 sensor
- VOC sensor
- Temperature sensor: Built-in

	Unit of measurement	Freshpoint 160-E Pro L07
Connected air duct size	mm	160
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	22
Power of electrical preheater	W	100
Unit current	A	0.62
Maximum airflow	m <sup>3</sup> /h	57
Sound pressure level LpA at 3 m	dB(A)	42
Heat recovery efficiency	%	88
Heat recovery efficiency, max	%	88
Heat exchanger material	-	Copper
Filter	-	G3
Transported air temperature (max)	°C	50
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Maximum wall thickness	mm	700

## Dimensions

D	L	L1
162	800	700

