


Freshpoint Eco 160-E L1


Smart HRV unit for single-room ventilation

- Power of electrical reheater: 160
- Air flow in heat recovery mode: 48
- Sound pressure level LpA at 3 m: 40
- Sound pressure level LpA at 1 m: 50
- Heat exchanger material: Ceramic
- Filter: G3
- Control: Smartphone
- Casing material: ABS Plastic
- Temperature sensor
- Heater


	Unit of measurement	Freshpoint Eco 160-E L1		
Phases	-	1		
Maximum supply voltage	V	240		
Minimum supply voltage	V	220		
Power supply frequency	Hz	50/60		
Rated power	W	3	5	8
Power of electrical reheater	W	160		
Unit current	A	0.93	0.94	0.95
Air flow in ventilation mode	m³/h	10	30	48
Air flow in heat recovery mode	m³/h	10	30	48
Sound pressure level LpA at 3 m	dB(A)	14	27	40
Sound pressure level LpA at 1 m	dB(A)	24	36	50
Heat recovery efficiency, max	%	90		
Heat exchanger material	-	Ceramic		
Filter	-	G3		
Transported air temperature (max)	°C	50		
Transported air temperature (min)	°C	-30		
Ingress protection rating	-	IPX4		
Ambient air humidity max	%	70		
Minimum wall thickness	mm	705		
Maximum wall thickness	mm	1000		

Dimensions

ØD	L	L1
162	1100	1000



Ecodesign



Trademark	Blauberg					
Model	Freshpoint Eco 160-E L1					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	77.2	A+	37.9	A	15.5	E
Type of ventilation unit	Bidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	Regenerative					
Thermal efficiency of heat recovery (%)	65					
Maximum flow rate (m³/h)	48					
Electric power input (W)	8					
Reference flow rate (m³/s)	0.01					
Specific power input (SPI) (W/(m³/h))	0.2					
Control typology	Local demand control					
Maximum internal leakage rates (%)	0.1					
Maximum external leakage rates (%)	0.9					
Mixing rate (%)	1					
Airflow sensitivity at +20 Pa and -20 Pa (%)	0.93					
The indoor/outdoor air tightness (m³/h)	7					
Sound power level (dB(A))	46					
Declared typology	RVU BVU					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	116		116		116	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	80		41		19	

Accessories

Other accessories

Name	Photo	Description
CPSO-200 Freshpoint 160		External compensator pad
CPSO-120 Freshpoint 160		External compensator pad

CPSO-80 Freshpoint 160		External compensator pad
CPSO-160 Freshpoint 160		External compensator pad
CPSO-40 Freshpoint 160		External compensator pad
MPS Freshpoint 160		Stainless steel cuff for external installation
SF Freshpoint G3		Filter (2 pcs.)
SF Freshpoint G4		Filter (2 pcs.)
SF Freshpoint G4 + carbon		Filter (2 pcs.)
KLW Freshpoint Eco 160 L1		Expansion kit for thick walls