



## Hi-Fi 125



Low noise and low power exhaust axial fan

- Sound pressure level LpA at 3 m: 32
- Casing material: Plastic
- Backdraft protection: Backdraft damper

	Unit of measurement	Hi-Fi 125
Connected air duct size	mm	125
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	18
Unit current	A	0.11
Maximum airflow	m <sup>3</sup> /h	155
Sound pressure level LpA at 3 m	dB(A)	32
Weight	kg	0.75
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IP44
Impeller material	-	Plastic
Article	-	8060922

### Dimensions

a	c	Ø d	e
180	85	124	41



## Ecodesign

Trademark	Blauberg					
Model	Hi-Fi 125					
Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a))	Cold		Average		Warm	
	-29.9	B	-13.5	E	-4.1	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Single speed					
Type of heat recovery system	None					
Maximum flow rate (m <sup>3</sup> /h)	155					
Electric power input (W)	18					
Reference flow rate (m <sup>3</sup> /s)	0.03					
Specific power input (SPI) (W/(m <sup>3</sup> /h))	0.116					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	52					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average		Warm		
	145	145		145		
The annual heating saved (AHS) (kWh/a)	Cold	Average		Warm		
	3355	1715		776		