




Iso-K 250 4D

Kitchen inline fans in sound-insulated casings with operational temperature of 120 °C


- Maximum airflow: 3500
- Sound pressure level LpA at 3 m: 51
- Sound insulation
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel


	Unit of measurement	Iso-K 250 4D
Connected air duct size	mm	250
Speed	-	1
Minimum supply voltage	V	400
Maximum supply voltage	V	400
Power supply frequency	Hz	50
Rated power	W	1500
Unit current	A	3.4
Maximum airflow	m ³ /h	3500
Sound pressure level LpA at 3 m	dB(A)	51
Weight	kg	40
Transported air temperature (max)	°C	120
Transported air temperature (min)	°C	-20
Ingress protection rating	-	IP54



Dimensions

∅ D	B	B1	H	H1	L	L1	L2	L3	L4
250	575	435	665	505	700	675	645	620	285





Ecodesign

Trademark	Blauberg
Model	Iso-K 250 4D
Type of ventilation unit	Unidirectional
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.723
Nominal external pressure (Pa)	468
Maximum external leakage rates (%)	2.7
Static efficiency (%)	20
Declared typology	NRVU UVU
Sound power level (dB(A))	71
Effective electric power input (kW)	1.49