


Iso-Primo EC 355 G1


Mixed-flow inline fans in sound-insulated casings with EC-motors



- Maximum airflow: 3500
- Sound pressure level LpA at 3 m: 48
- Sound insulation
- Motor type: EC
- Control: Speed controller
- Impeller type: Mixed-flow
- Casing material: Galvanized steel
- Installation in any position
- Cable with mains plug
- Temperature sensor: Remote



	Unit of measurement	Iso-Primo EC 355 G1
Connected air duct size	mm	355
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	353
Unit current	A	1.56
Maximum airflow	m ³ /h	3500
rotation speed at 50hz	-	2470
Sound pressure level LpA at 3 m	dB(A)	48
Weight	kg	20.7
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44








Dimensions

Ø D	Ø D1	H	L	L1
354	412	471	601	739




Accessories


Other accessories

Name	Photo	Description
SD 355/1200		Silencers for round ducts
SD 355/900		Silencers for round ducts
SD 355/600		Silencers for round ducts

Other accessories

Name	Photo	Description
VKA 355		Air dampers for round ducts

Other accessories

Name	Photo	Description
CDT E/0-10		Speed control for EC motors