


Iso-Primo EC 400 W




Mixed-flow inline fans in sound-insulated casings with EC-motors

- Maximum airflow: 5415
- Sound pressure level LpA at 3 m: 49
- Sound insulation
- Motor type: EC
- Impeller type: Mixed-flow
- Casing material: Galvanized steel
- Installation in any position
- Cable with mains plug



	Unit of measurement	Iso-Primo EC 400 W
Connected air duct size	mm	400
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	726
Unit current	A	4.8
Maximum airflow	m ³ /h	5415
rotation speed at 50hz	-	2580
Sound pressure level LpA at 3 m	dB(A)	49
Weight	kg	22.8
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ambient air temperature min	°C	1
Ambient air temperature max	°C	40
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44






Dimensions

Ø D	Ø D1	H	L	L1
399	460	517	648	785




Accessories



Other accessories

Name	Photo	Description
CDT E/0-10		Speed control for EC motors

Other accessories

Name	Photo	Description
VKA 400		Air dampers for round ducts

Other accessories

Name	Photo	Description
SD 400/1200		Silencers for round ducts
SD 400/900		Silencers for round ducts