



# Kamin-ER 125 KF+GF

Chimney centrifugal fans

- Maximum airflow: 350
- Sound pressure level LpA at 3 m: 37
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel
- Installation in any position

|                                   | Unit of measurement | Kamin-ER 125 KF+GF |
|-----------------------------------|---------------------|--------------------|
| Connected air duct size           | mm                  | 125                |
| Phases                            | -                   | 1                  |
| Minimum supply voltage            | V                   | 230                |
| Maximum supply voltage            | V                   | 230                |
| Power supply frequency            | Hz                  | 50                 |
| Rated power                       | W                   | 32                 |
| Unit current                      | A                   | 0.14               |
| Maximum airflow                   | m <sup>3</sup> /h   | 350                |
| rotation speed at 50hz            | -                   | 1335               |
| Sound pressure level LpA at 3 m   | dB(A)               | 37                 |
| Weight                            | kg                  | 9.4                |
| Transported air temperature (max) | °C                  | 150                |
| Ingress protection rating         | -                   | IPX2               |

## Dimensions

| Ø D | B   | H   | H1  | L   | P  |
|-----|-----|-----|-----|-----|----|
| 124 | 245 | 580 | 530 | 260 | 50 |

