



# Kamin-ER 160

Chimney fans

- Maximum airflow: 470
- Sound pressure level LpA at 3 m: 39
- Motor type: AC
- Impeller type: Centrifugal forward curved blades
- Casing material: Galvanized steel
- Installation in any position

|                                   | Unit of measurement | Kamin-ER 160 |
|-----------------------------------|---------------------|--------------|
| Connected air duct size           | mm                  | 160          |
| Phases                            | -                   | 1            |
| Minimum supply voltage            | V                   | 230          |
| Maximum supply voltage            | V                   | 230          |
| Power supply frequency            | Hz                  | 50           |
| Rated power                       | W                   | 44           |
| Unit current                      | A                   | 0.19         |
| Maximum airflow                   | m <sup>3</sup> /h   | 470          |
| rotation speed at 50hz            | -                   | 1110         |
| Sound pressure level LpA at 3 m   | dB(A)               | 39           |
| Weight                            | kg                  | 6.8          |
| Transported air temperature (max) | °C                  | 150          |
| Ingress protection rating         | -                   | IPX2         |

## Dimensions

| Ø D | B   | H   | H1  | L   | P  |
|-----|-----|-----|-----|-----|----|
| 159 | 285 | 320 | 270 | 300 | 50 |

