

# KOMFORT D6B 150 R

Brand new smart air solution for ultra-low energy consumption buildings



- Maximum airflow: 150
- Sound pressure level LpA at 3 m: 31
- Heat exchanger type: Counter flow
- Extract filter: G4
- Supply filter: G4 + F7
- Motor type: DC
- Control: Wired control panel
- Humidity sensor
- CO2 sensor
- VOC sensor
- PM2.5 sensor
- Temperature sensor

|                                 | Unit of measurement | KOMFORT D6B 150 R |
|---------------------------------|---------------------|-------------------|
| Connected air duct size         | mm                  | 146               |
| Minimum supply voltage          | V                   | 220               |
| Maximum supply voltage          | V                   | 220               |
| Power supply frequency          | Hz                  | 50                |
| Rated power                     | W                   | 45                |
| Unit current                    | A                   | 0.21              |
| Maximum airflow                 | m <sup>3</sup> /h   | 150               |
| Sound pressure level LpA at 3 m | dB(A)               | 31                |
| Heat recovery efficiency, max   | %                   | 81                |
| Heat exchanger type             | -                   | Counter flow      |
| Weight                          | kg                  | 42                |
| Extract filter                  | -                   | G4                |
| Supply filter                   | -                   | G4 + F7           |

## Dimensions

