



## KOMFORT GLA D250

The GLA series is the first in the Blauberg household series to adopt BlauFion nanoparticle technology, which actively sterilizes and disinfects the air to ensure clean and healthy indoor air

- Maximum airflow: 250
- Sound pressure level LpA at 3 m: 36
- Heat exchanger type: Counter flow
- Extract filter: G4 + G3 composite filter
- Supply filter: G4 + G3 composite screen, H13 silver ion composite screen
- Sound insulation
- Control: Smartphone
- Casing material: Coated steel

	Unit of measurement	KOMFORT GLA D250		
Connected air duct size	mm	150		
Speed	-	3		
Minimum supply voltage	V	220		
Maximum supply voltage	V	220		
Rated power	W	90	60	30
Unit current	A	0.41	0.27	0.13
Maximum airflow	m <sup>3</sup> /h	250	175	100
Sound pressure level LpA at 3 m	dB(A)	36	33	30
Heat recovery efficiency, max	%	72		
Heat exchanger type	-	Counter flow		
Weight	kg	29		
Extract filter	-	G4 + G3 composite filter		
Supply filter	-	G4 + G3 composite screen, H13 silver ion composite screen		
Transported air temperature (max)	°C	1		
Transported air temperature (min)	°C	40		

### Dimensions

B	B1	B2	B3	B4	B5	B6	L	L1	L2	H	H1	H2	H3	H4
664	59	59	252	246	107	344	804	686	59	246	120	100	120	100

