



## KOMFORT GLA D350

The GLA series is the first in the Blauberg household series to adopt BlauFion nanoparticle technology, which actively sterilizes and disinfects the air to ensure clean and healthy indoor air

- Maximum airflow: 350
- Sound pressure level LpA at 3 m: 38
- Heat exchanger type: Counter flow
- Extract filter: G4 + G3 composite filter
- Supply filter: G4 + G3 composite screen, H13 silver ion composite screen
- Sound insulation
- Control: Smartphone
- Casing material: Coated steel

	Unit of measurement	KOMFORT GLA D350		
Connected air duct size	mm	150		
Speed	-	3		
Minimum supply voltage	V	220		
Maximum supply voltage	V	220		
Rated power	W	125	72	40
Unit current	A	0.57	0.33	0.18
Maximum airflow	m <sup>3</sup> /h	350	245	140
Sound pressure level LpA at 3 m	dB(A)	38	36	32
Heat recovery efficiency, max	%	73		
Heat exchanger type	-	Counter flow		
Weight	kg	35		
Extract filter	-	G4 + G3 composite filter		
Supply filter	-	G4 + G3 composite screen, H13 silver ion composite screen		
Transported air temperature (max)	°C	1		
Transported air temperature (min)	°C	40		

### Dimensions

B	B1	B2	B3	B4	B5	B6	L	L1	L2	H	H1	H2	H3	H4
764	59	59	252	299	107	444	804	686	59	246	120	100	120	100

