



KOMFORT GLA D350

The GLA series is the first in the Blauberg household series to adopt BlauFion nanoparticle technology, which actively sterilizes and disinfects the air to ensure clean and healthy indoor air

- Maximum airflow: 350
- Sound pressure level LpA at 3 m: 38
- Heat exchanger type: Counter flow
- Extract filter: G4 + G3 composite filter
- Supply filter: G4 + G3 composite screen, H13 silver ion composite screen
- Sound insulation
- Control: Smartphone
- Casing material: Coated steel

| | Unit of measurement | KOMFORT GLA D350 | | |
|-----------------------------------|---------------------|---|------|------|
| Connected air duct size | mm | 150 | | |
| Speed | - | 3 | | |
| Minimum supply voltage | V | 220 | | |
| Maximum supply voltage | V | 220 | | |
| Rated power | W | 125 | 72 | 40 |
| Unit current | A | 0.57 | 0.33 | 0.18 |
| Maximum airflow | m ³ /h | 350 | 245 | 140 |
| Sound pressure level LpA at 3 m | dB(A) | 38 | 36 | 32 |
| Heat recovery efficiency, max | % | 73 | | |
| Heat exchanger type | - | Counter flow | | |
| Weight | kg | 35 | | |
| Extract filter | - | G4 + G3 composite filter | | |
| Supply filter | - | G4 + G3 composite screen, H13 silver ion composite screen | | |
| Transported air temperature (max) | °C | 1 | | |
| Transported air temperature (min) | °C | 40 | | |

Dimensions

| B | B1 | B2 | B3 | B4 | B5 | B6 | L | L1 | L2 | H | H1 | H2 | H3 | H4 |
|-----|----|----|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|
| 764 | 59 | 59 | 252 | 299 | 107 | 444 | 804 | 686 | 59 | 246 | 120 | 100 | 120 | 100 |

