



KOMFORT GLA D350 F

The GLA series is the first in the Blauberg household series to adopt BlauFion nanoparticle technology, which actively sterilizes and disinfects the air to ensure clean and healthy indoor air

- Maximum airflow: 350
- Sound pressure level LpA at 3 m: 38
- Heat exchanger type: Counter flow
- Extract filter: G4 + G3 composite filter
- Supply filter: G4 + G3 composite screen, H13 silver ion composite screen
- Sound insulation
- Control: Smartphone
- Casing material: Coated steel
- BlauFion module

	Unit of measurement	KOMFORT GLA D350 F		
Connected air duct size	mm	150		
Speed	-	3		
Minimum supply voltage	V	220		
Maximum supply voltage	V	220		
Rated power	W	125	72	40
Unit current	A	0.57	0.33	0.18
Maximum airflow	m ³ /h	350	245	140
Sound pressure level LpA at 3 m	dB(A)	38	36	32
Heat recovery efficiency, max	%	73		
Heat exchanger type	-	Counter flow		
Weight	kg	35		
Extract filter	-	G4 + G3 composite filter		
Supply filter	-	G4 + G3 composite screen, H13 silver ion composite screen		
Transported air temperature (max)	°C	1		
Transported air temperature (min)	°C	40		

Dimensions

B	B1	B2	B3	B4	B5	B6	L	L1	L2	H	H1	H2	H3	H4
764	59	59	252	299	107	444	804	686	59	246	120	100	120	100

