




Line 100 ST

Extract fans

- Maximum airflow: 95
- Sound pressure level LpA at 3 m: 34
- Motor type: AC
- Pull cord
- Timer: Turn off timer, Turn on timer

| | Unit of measurement | Line 100 ST |
|---------------------------------|---------------------|-------------|
| Connected air duct size | mm | 100 |
| Speed | - | 1 |
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 14 |
| Unit current | A | 0.085 |
| Maximum airflow | m ³ /h | 95 |
| Sound pressure level LpA at 3 m | dB(A) | 34 |
| Weight | kg | 0.58 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 40 |
| Ingress protection rating | - | IP34 |



Dimensions

| a | b | c | Ø d | e |
|-----|-----|-----|-----|------|
| 150 | 120 | 109 | 100 | 12.5 |



Ecodesign



| | | | | | | |
|---|----------------|---|---------|---|------|---|
| Trademark | Blauberg | | | | | |
| Model | Line 100 ST | | | | | |
| Specific energy consumption (SEC) (kWh/(m ² /a)) | Cold | | Average | | Warm | |
| | 0 | B | 0 | E | 0 | F |
| Type of ventilation unit | Unidirectional | | | | | |
| Type of drive installed | Single speed | | | | | |
| Type of heat recovery system | None | | | | | |
| Maximum flow rate (m ³ /h) | 0 | | | | | |
| Electric power input (W) | 0 | | | | | |
| Reference flow rate (m ³ /s) | 0 | | | | | |
| Specific power input (SPI) (W/(m ³ /h)) | 0 | | | | | |
| Control typology | Manual control | | | | | |
| Maximum external leakage rates (%) | 0 | | | | | |
| Sound power level (dB(A)) | 0 | | | | | |
| Declared typology | RVU UVU | | | | | |
| The annual electricity consumption (AEC) (kWh/a) | Cold | | Average | | Warm | |
| | 0 | | 0 | | 0 | |
| The annual heating saved (AHS) (kWh/a) | Cold | | Average | | Warm | |
| | 0 | | 0 | | 0 | |