



Quatro 150

Extract fans with decorative front panel

- Maximum airflow: 265
- Sound pressure level LpA at 3 m: 37
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper


	Unit of measurement	Quatro 150
Connected air duct size	mm	150
Speed	-	1
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Rated power	W	24
Unit current	A	0.13
Maximum airflow	m ³ /h	265
Sound pressure level LpA at 3 m	dB(A)	37
Ingress protection rating	-	IP34

Dimensions

a	a1	b	c	Ø d	e
236	207	165	157	150	38



Ecodesign



Trademark	Blaubeerg					
Model	Quatro 150					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-32	B	-15	E	-6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m³/h)	265					
Electric power input (W)	24					
Reference flow rate (m³/s)	0.052					
Specific power input (SPI) (W/(m³/h))	0.058					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	57					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average	Warm			
	100	100	100			
The annual heating saved (AHS) (kWh/a)	Cold	Average	Warm			
	3400	1700	800			