



Sileo Max 150 TR

High efficient exhaust fans with stylish design for new enhanced comfort

- Maximum airflow: 370
- Sound pressure level LpA at 3 m: 38
- Motor type: AC
- Backdraft protection: Backdraft damper
- Timer: Turn off timer, Turn on timer

	Unit of measurement	Sileo Max 150 TR	
Connected air duct size	mm	150	
Speed	-	2	
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50/60	
Rated power	W	19	22
Unit current	A	0.09	0.1
Maximum airflow	m ³ /h	280	370
Sound pressure level LpA at 3 m	dB(A)	32	38
Weight	kg	1.33	
Ambient air temperature min	°C	1	
Ambient air temperature max	°C	40	
Ingress protection rating	-	IP45	

Dimensions

a	b	c	Ø d	e
190	214	98	148	32



Ecodesign



Trademark	Blauberg					
Model	Sileo Max 150 TR					
Specific energy consumption (SEC) (kWh/(m ² /a))	Cold		Average		Warm	
	-31.4	B	-15	E	-5.6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	2-speed					
Type of heat recovery system	None					
Maximum flow rate (m ³ /h)	370					
Electric power input (W)	22					
Reference flow rate (m ³ /s)	0.078					
Specific power input (SPI) (W/(m ³ /h))	0.068					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Sound power level (dB(A))	52					
Declared typology	RVU UVU					
The annual electricity consumption (AEC) (kWh/a)	Cold	Average		Warm		
	85	85		85		
The annual heating saved (AHS) (kWh/a)	Cold	Average		Warm		
	3355	1715		776		