



Trio 150 S

Low noise and low power extract axial fan

- Maximum airflow: 255
- Sound pressure level LpA at 3 m: 35
- Motor type: AC
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Pull cord

| | Unit of measurement | Trio 150 S |
|---------------------------------|---------------------|------------|
| Connected air duct size | mm | 150 |
| Speed | - | 1 |
| Minimum supply voltage | V | 220 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50 |
| Rated power | W | 28 |
| Unit current | A | 0.21 |
| Maximum airflow | m ³ /h | 255 |
| Sound pressure level LpA at 3 m | dB(A) | 35 |
| Weight | kg | 0.97 |
| Ambient air temperature min | °C | 1 |
| Ambient air temperature max | °C | 40 |
| Ingress protection rating | - | IP44 |

Dimensions

| a | c | Ø d | e |
|-----|-----|-----|----|
| 206 | 100 | 148 | 23 |



Ecodesign



| | | | | | | |
|---|----------------|---------|---------|------|------|---|
| Trademark | Blauberg | | | | | |
| Model | Trio 150 S | | | | | |
| Specific energy consumption (SEC) (kWh/(m ² /a)) | Cold | | Average | | Warm | |
| | -30.1 | B | -13.7 | E | -4.3 | F |
| Type of ventilation unit | Unidirectional | | | | | |
| Type of drive installed | Single speed | | | | | |
| Type of heat recovery system | None | | | | | |
| Maximum flow rate (m ³ /h) | 255 | | | | | |
| Electric power input (W) | 28 | | | | | |
| Reference flow rate (m ³ /s) | 0.05 | | | | | |
| Specific power input (SPI) (W/(m ³ /h)) | 0.11 | | | | | |
| Control typology | Manual control | | | | | |
| Maximum external leakage rates (%) | 2.7 | | | | | |
| Declared typology | RVU UVU | | | | | |
| Sound power level (dB(A)) | 55 | | | | | |
| The annual electricity consumption (AEC) (kWh/a) | Cold | Average | | Warm | | |
| | 138 | 138 | | 138 | | |
| The annual heating saved (AHS) (kWh/a) | Cold | Average | | Warm | | |
| | 3355 | 1715 | | 776 | | |