



## Valeo-BP 35/60

Mono-pipe ventilation exhaust centrifugal fans

- Maximum airflow: 63
- Sound pressure level LpA at 3 m: 36
- Control: Wired control panel
- Casing material: Plastic
- Backdraft protection: Backdraft damper

|                                 | Unit of measurement | Valeo-BP 35/60 |      |
|---------------------------------|---------------------|----------------|------|
| Connected air duct size         | mm                  | 80             |      |
| Speed                           | -                   | 2              |      |
| Minimum supply voltage          | V                   | 220            |      |
| Maximum supply voltage          | V                   | 240            |      |
| Power supply frequency          | Hz                  | 50             |      |
| Rated power                     | W                   | 15             | 25   |
| Unit current                    | A                   | 0.12           | 0.14 |
| Maximum airflow                 | m <sup>3</sup> /h   | 35             | 63   |
| Sound pressure level LpA at 3 m | dB(A)               | 27             | 36   |
| Weight                          | kg                  | 2.7            |      |
| Ambient air temperature min     | °C                  | 1              |      |
| Ambient air temperature max     | °C                  | 40             |      |
| Ingress protection rating       | -                   | IP55           |      |

### Dimensions




## Ecodesign



|   |                |   |         |   |      |   |
|---|----------------|---|---------|---|------|---|
| Trademark   | Blauberg       |   |         |   |      |   |
| Model   | Valeo-BP 35/60 |   |         |   |      |   |
| Specific energy consumption (SEC) (kWh/(m <sup>2</sup> /a)) | Cold           |   | Average |   | Warm |   |
|   | -20.1          | D | -3.7    | F | 5.7  | G |
| Type of ventilation unit                                    | Unidirectional |   |         |   |      |   |
| Type of drive installed                                     | 2-speed        |   |         |   |      |   |
| Type of heat recovery system                                | None           |   |         |   |      |   |
| Maximum flow rate (m <sup>3</sup> /h)                       | 63             |   |         |   |      |   |
| Electric power input (W)                                    | 25             |   |         |   |      |   |
| Reference flow rate (m <sup>3</sup> /s)                     | 0.01           |   |         |   |      |   |
| Reference pressure difference (Pa)                          | 50             |   |         |   |      |   |
| Specific power input (SPI) (W/(m <sup>3</sup> /h))          | 0.429          |   |         |   |      |   |
| Control typology  | Manual control |   |         |   |      |   |
| Maximum external leakage rates (%)                          | 2.7            |   |         |   |      |   |
| Sound power level (dB(A))                                   | 47             |   |         |   |      |   |
| Declared typology   | RVU UVU        |   |         |   |      |   |
| The annual electricity consumption (AEC) (kWh/a)            | Cold           |   | Average |   | Warm |   |
|   | 537            |   | 537     |   | 537  |   |
| The annual heating saved (AHS) (kWh/a)                      | Cold           |   | Average |   | Warm |   |
|   | 3355           |   | 1715    |   | 776  |   |

## Accessories

### Other accessories

| Name                    | Photo   | Description        |
|-------------------------|---|--------------------|
| <a href="#">CDP-3/5</a> |  | Multi-speed switch |