



# Valeo-BPL 35/60 H

Mono-pipe ventilation exhaust centrifugal fans

- Maximum airflow: 63
- Sound pressure level LpA at 3 m: 36
- Control: Wired control panel
- Casing material: Plastic
- Backdraft protection: Backdraft damper
- Motion sensor
- Humidity sensor: Built-in
- Light sensor: Built-in
- Timer: Built-in

|                                 | Unit of measurement | Valeo-BPL 35/60 H |      |
|---------------------------------|---------------------|-------------------|------|
| Connected air duct size         | mm                  | 80                |      |
| Speed                           | -                   | 2                 |      |
| Minimum supply voltage          | V                   | 220               |      |
| Maximum supply voltage          | V                   | 240               |      |
| Power supply frequency          | Hz                  | 50                |      |
| Rated power                     | W                   | 15                | 25   |
| Unit current                    | A                   | 0.12              | 0.14 |
| Maximum airflow                 | m <sup>3</sup> /h   | 35                | 63   |
| Sound pressure level LpA at 3 m | dB(A)               | 27                | 36   |
| Weight                          | kg                  | 2.7               |      |
| Ambient air temperature min     | °C                  | 1                 |      |
| Ambient air temperature max     | °C                  | 40                |      |
| Ingress protection rating       | -                   | IP55              |      |

## Dimensions



## Accessories

### Other accessories

| Name                    | Photo  | Description        |
|-------------------------|--|--------------------|
| <a href="#">CDP-3/5</a> |  | Multi-speed switch |