

AirWall

Single-room wall mounting HRV with high-efficiency HRV or ERV counter-flow recovery and app control. Cold-climate versions add integrated heaters plus mechanical supply and gravity exhaust dampers

- Heat exchanger type: Counter flow
- Heat exchanger material: Polystyrene, Enthalpy
- Casing material: ABS Plastic
- Humidity sensor: Built-in
- CO2 sensor: Optional

Lineup	Maximum airflow, m³/h	Maximum airflow (Boost mode), m³/h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Reheater	Preheater	Humidity sensor	CO2 sensor
AirWall	80	150	28	98	✕	✕	Built-in	Optional
AirWall BLK	80	150	28	98	✕	✕	Built-in	Optional
AirWall E	80	150	28	98	✕	Electric	Built-in	Optional
AirWall E BLK	80	150	28	98	✕	Electric	Built-in	Optional
AirWall E2	80	150	28	98	Electric	Electric	Built-in	Optional
AirWall E2 BLK	80	150	28	98	Electric	Electric	Built-in	Optional

 AirWall ERV	80	150	27	85	✖	✖	Built-in	Optional
 AirWall ERV BLK	80	150	27	85	✖	✖	Built-in	Optional
 AirWall E ERV	80	150	27	85	✖	Electric	Built-in	Optional
 AirWall E ERV BLK	80	150	27	85	✖	Electric	Built-in	Optional
 AirWall E2 ERV	80	150	27	85	Electric	Electric	Built-in	Optional
 AirWall E2 ERV BLK	80	150	27	85	Electric	Electric	Built-in	Optional