









# BlauAIR RH

Floor mounted heat recovery units



- Heat exchanger type: Rotary
- Sound insulation
- Motor type: EC
- Bypass: Auto
- Reheater: Optional
- Preheater: Optional
- BMS protocol: Bacnet
- Control: Wired control panel
- Casing material: Aluzinc steel

Lineup	Connected air duct size, mm	Speed	Phases	Maximum supply voltage, V	Maximum airflow, m <sup>3</sup> /h	Sound pressure level LpA at 3 m, dB(A)	Heat exchanger material	Extract filter	Supply filter	Reheater	Preheater	BMS protocol
 BlauAIR RH 800	315	1	1	240	800	34	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 1200	315	1	1	240	1200	35	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 1500	600x350	1	1	240	1500	37	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 2500	600x350	1	1	277	2500	37	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 3500	700x400	1	3	480	3500	35	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 5000	1000x500	1	3	480	5000	32	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 6000	1000x500	1	3	480	6000	32	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet
 BlauAIR RH 9000	1200x600	1	3	480	9000	32	Aluminum	ePM1 55% (ISO 16890)-F7 (EN779)	ePM1 55% (ISO 16890)-F7 (EN779)	Optional	Optional	Bacnet