






















Hi-Fi

Low noise and low power exhaust axial fan

- Casing material: Plastic
- Timer: Turn off timer, Turn on timer
- Humidity sensor

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h	Sound pressure level L _{pA} at 3 m, dB(A)	Pull cord	Timer	Humidity sensor
 Hi-Fi 100	100	8	85	27			
 Hi-Fi 100 S	100	8	85	27	✓		
 Hi-Fi 100 T	100	8	85	27		✓	
 Hi-Fi 100 TR	100	8	85	27		✓	
 Hi-Fi 100 ST	100	8	85	27	✓	✓	
 Hi-Fi 100 H	100	8	85	27		✓	✓

 Hi-Fi 100 SH	100	8	85	27	✓	✓	✓
 Hi-Fi 100 (220-240V/60Hz)	100						
 Hi-Fi 100 (220-240V/60Hz) S	100				✓		
 Hi-Fi 100 (220-240V/60Hz) T	100					✓	
 Hi-Fi 100 (220-240V/60Hz) TR	100					✓	
 Hi-Fi 100 (220-240V/60Hz) ST	100				✓	✓	
 Hi-Fi 100 (220-240V/60Hz) H	100					✓	✓
 Hi-Fi 100 (220-240V/60Hz) SH	100				✓	✓	✓
 Hi-Fi 125	125	18	155	32			
 Hi-Fi 125 S	125	18	155	32	✓		
 Hi-Fi 125 T	125	18	155	32		✓	
 Hi-Fi 125 TR	125	18	155	32		✓	
 Hi-Fi 125 ST	125	18	155	32	✓	✓	

 Hi-Fi 125 H	125	18	155	32		✓	✓
 Hi-Fi 125 SH	125	18	155	32	✓	✓	✓