# Hybrid Max

Decentralized unit for the small offices, facilities, classrooms and living spaces

- Heat exchanger type: Counter flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- BMS protocol: ModBus
- Control: Wireless control panel
- Casing material: Galvanized steel
- Humidity sensor: Optional
- Reheater: Electric
- Enthalpy heat exchanger

| Lineup | Rated power, W | Maximum airflow, $m^3/h$ | Sound pressure level LpA at 3 m, dB(A) | Heat recovery efficiency, max, % | Enthalpy heat exchanger | Reheater | Control | Mounting type | Humidity sensor |
|---|---|---|---|---|---|---|---|---|---|
| Hybrid Max S14 | 58 | 160 | 32 | 95 | ✗ | ✗ | Wireless control panel | Suspended | ✓ |
| Hybrid Max S21 | 58 | 160 | 32 | 95 | ✗ | ✗ | Wireless control panel | Suspended | ✓ |
| Hybrid Max E S21 | 58 | 160 | 32 | 95 | ✗ | Electric | Wireless control panel | Suspended | ✓ |
| Hybrid Max E ERV S21 | 58 | 160 | 32 | 89 | ✓ | Electric | Wireless control panel | Suspended | ✓ |
| Hybrid Max ERV S14 | 58 | 160 | 32 | 89 | ✓ | ✗ | Wireless control panel | Suspended | ✓ |
| Hybrid Max ERV S21 | 58 | 160 | 32 | 89 | ✓ | ✗ | Wireless control panel | Suspended | ✓ |
| Hybrid Max S21 | | | | | | | | | |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Hybrid Max S21 | | | | | | | | | |
| Hybrid Max E S21 | | | | | | | | | |