Hybrid Max

Decentralized unit for the small offices, facilities, classrooms and living spaces

- Heat exchanger type: Counter flow
- Sound insulation
- Motor type: EC
- Bypass: Auto
- BMS protocol: ModBus
- Control: Wireless control panel
- Casing material: Galvanized steel
- Humidity sensor: Optional
- Reheater: Electric
- Enthalpy heat exchanger

Lineup	Rated power, W	Maximum airflow, m^3/h	Sound pressure level LpA at 3 m, dB(A)	Heat recovery efficiency, max, %	Enthalpy heat exchanger	Reheater	Control	Mounting type	Humidity sensor
Hybrid Max S14	58	160	32	95	✗	✗	Wireless control panel	Suspended	✓
Hybrid Max S21	58	160	32	95	✗	✗	Wireless control panel	Suspended	✓
Hybrid Max E S21	58	160	32	95	✗	Electric	Wireless control panel	Suspended	✓
Hybrid Max E ERV S21	58	160	32	89	✓	Electric	Wireless control panel	Suspended	✓
Hybrid Max ERV S14	58	160	32	89	✓	✗	Wireless control panel	Suspended	✓
Hybrid Max ERV S21	58	160	32	89	✓	✗	Wireless control panel	Suspended	✓
Hybrid Max S21									

Hybrid Max S21									
Hybrid Max E S21									