








Iso-K

Kitchen inline fans in sound-insulated casings with operational temperature of 120 °C

• Sound-insulated casing
• Impeller type: Centrifugal impeller with forward curved blades, Centrifugal impeller with backward curved blades
• Casing material: Galvanized steel

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m³/h
 Iso-K 150 4D	150	180	730
 Iso-K 150 4E	150	180	700
 Iso-K 160 4D	160	180	730
 Iso-K 160 4E	160	180	700
 Iso-K 200 4D	200	750	1650
 Iso-K 200 4E	200	550	1600
 Iso-K 250 4D	250	1500	3500

 Iso-K 250 4E	250	1500	3400
 Iso-K 315 2D	315	1225	4710
 Iso-K 315 2E	315	1531	4695
 Iso-K 315 4D	315	184	2040
 Iso-K 315 4E	315	304	1970
 Iso-K 355 2D	355	3145	6185
 Iso-K 355 2E	355	2621	6570
 Iso-K 355 4D	355	405	3155
 Iso-K 355 4E	355	393	3545
 Iso-K 400 4D	400	785	5098
 Iso-K 400 4E	400	1048	5392
 Iso-K 400 6D	400	357	2966
 Iso-K 400 6E	400	362	2915

 Iso-K 450 4D	450	1350	7840
 Iso-K 450 4E	450	1570	8138
 Iso-K 450 6D	450	454	4991
 Iso-K 450 6E	450	594	5299