








Iso-Primo






Mixed-flow inline fans in sound-insulated casings



- Sound insulation
- Motor type: AC
- Impeller type: Mixed-flow
- Casing material: Galvanized steel
- Timer: Turn off timer
- Control: Speed controller

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m ³ /h	Cable with mains plug	Temperature sensor	Timer
 Iso-Primo 200	200	113	1110	✗	✗	
 Iso-Primo 200 T	200	113	1110	✗	✗	✓
 Iso-Primo 200 US	200	113	1110	✗	✗	
 Iso-Primo 200 G1	200	113	1110	✓	✓	
 Iso-Primo 200 W	200	113	1110	✓	✗	
 Iso-Primo 250	250	188	1670	✗	✗	
 Iso-Primo 250 T	250	188	1670	✗	✗	✓

 Iso-Primo 250 US	250	188	1670	✗	✗	
 Iso-Primo 250 G1	250	188	1670	✓	✓	
 Iso-Primo 250 W	250	188	1670	✓	✗	
 Iso-Primo 315	315	148	2300			
 Iso-Primo 315 T	315	148	2300			✓
 Iso-Primo 315 US	315	148	2300			
 Iso-Primo 315 G1	315	148	2300	✓	✓	
 Iso-Primo 315 W	315	148	2300	✓		
 Iso-Primo 355	355	150	2360			
 Iso-Primo 355 T	355	150	2360			✓
 Iso-Primo 355 US	355	150	2360			
 Iso-Primo 355 G1	355	150	2360	✓	✓	
 Iso-Primo 355 W	355	150	2360	✓		

 Iso-Primo 400	400	224	3185			
 Iso-Primo 400 T	400	224	3185			✓
 Iso-Primo 400 US	400	224	3185			
 Iso-Primo 400 G1	400	224	3185	✓	✓	
 Iso-Primo 400 W	400	224	3185	✓		