







# Iso-Primo EC

Sound-insulated inline mixed-flow fans with EC motor



- Sound insulation
- Motor type: EC
- Impeller type: Mixed-flow
- Casing material: Galvanized steel
- Timer: Turn off timer
- Control: Speed controller

Lineup	Connected air duct size, mm	Rated power, W	Maximum airflow, m <sup>3</sup> /h	Cable with mains plug	Temperature sensor	Timer
 Iso-Primo EC 200	200	121	1210	✗	✗	
 Iso-Primo EC 200 T	200	121	1210	✗	✗	✓
 Iso-Primo EC 200 G1	200	121	1210	✓	✓	
 Iso-Primo EC 200 W	200	121	1210	✓	✗	
 Iso-Primo EC 250	250	168	1750	✗	✗	
 Iso-Primo EC 250 T	250	168	1750	✗	✗	✓

 Iso-Primo EC 250 G1	250	168	1750	✓	✓	
 Iso-Primo EC 250 W	250	168	1750	✓	✗	
 Iso-Primo EC 315	315	353	3090			
 Iso-Primo EC 315 T	315	353	3090			✓
 Iso-Primo EC 315 G1	315	353	3090	✓	✓	
 Iso-Primo EC 315 W	315	353	3090	✓		
 Iso-Primo EC 355	355	353	3500			
 Iso-Primo EC 355 T	355	353	3500			✓
 Iso-Primo EC 355 G1	355	353	3500	✓	✓	
 Iso-Primo EC 355 W	355	353	3500	✓		
 Iso-Primo EC 400	400	726	5415			
 Iso-Primo EC 400 T	400	726	5415			✓
 Iso-Primo EC 400 G1	400	726	5415	✓	✓	

 Iso-Primo EC 400 W	400	726	5415	✓		
------------------------------------------------------------------------------------------------------	-----	-----	------	---	--	--