

Iso-Primo EC

Mixed-flow inline fans in sound-insulated casings with EC-motors

- Sound-insulated casing
- Impeller type: Mixed-flow
- Casing material: Galvanized steel

Lineup	Connected air duct size, mm	Phases	Rated power, W	Maximum airflow, m³/h	Temperature sensor	Timer	Number of speeds
Iso-Primo EC 200	200	1	121	1210	✕		1
Iso-Primo EC 200 T	200	1	121	1210	✕	Turn off timer	1
Iso-Primo EC 200 G1	200	1	121	1210	Remote		1
Iso-Primo EC 200 W	200	1	121	1210	✕		1
Iso-Primo EC 250	250	1	168	1750	✕		1
Iso-Primo EC 250 T	250	1	168	1750	✕	Turn off timer	1
Iso-Primo EC 250 G1	250	1	168	1750	Remote		1

 Iso-Primo EC 250 W	250	1	168	1750	✕		1
 Iso-Primo EC 315	315	1	353	3090			1
 Iso-Primo EC 315 T	315	1	353	3090		Turn off timer	1
 Iso-Primo EC 315 G1	315	1	353	3090	Remote		1
 Iso-Primo EC 315 W	315	1	353	3090			1
 Iso-Primo EC 355	355	1	353	3500			1
 Iso-Primo EC 355 T	355	1	353	3500		Turn off timer	1
 Iso-Primo EC 355 G1	355	1	353	3500	Remote		1
 Iso-Primo EC 355 W	355	1	353	3500			1
 Iso-Primo EC 400 T	400	1	726	5415		Turn off timer	1
 Iso-Primo EC 400 G1	400	1	726	5415	Remote		1
 Iso-Primo EC 400 W	400	1	726	5415			1
 Iso-Primo EC 400	400	1	726	5415			1